

MATERIAL SAFETY DATA SHEET

5053Q
09 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

| | | | |
|-----------------------|---------------------------------------------------------|--------------|----|
| PRODUCT NUMBER | | HMS CODES | |
| 5053Q | | Health | 2* |
| | | Flammability | 0 |
| | | Reactivity | 0 |
| PRODUCT NAME | COLORPLACE* Interior Latex Flat Wall Paint, Accent Base | | |
| MANUFACTURER'S NAME | EMERGENCY TELEPHONE NO. | | |
| Distributed by | (216) 566-2917 | | |
| WAL-MART Stores Inc. | | | |
| Bentonville, AR 72716 | | | |
| DATE OF PREPARATION | INFORMATION TELEPHONE NO. | | |
| 20-SEP-02 | (216) 566-2902 | | |

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

| % by WT | CAS No. | INGREDIENT | UNITS | VAPOR PRESSURE |
|---------|------------|------------------|--------------------------|----------------|
| 2 | 107-21-1 | Ethylene Glycol. | | |
| | | ACGIH TLV | 50 ppm CEILING | 0.12 mm |
| | | OSHA PEL | 50 ppm CEILING | |
| 0.1 | 14464-46-1 | Cristobalite | | |
| | | ACGIH TLV | 0.05 mg/m3 as Resp. Dust | |
| | | OSHA PEL | 0.05 mg/m3 as Resp. Dust | |
| 6 | 12001-26-2 | Mica | | |
| | | ACGIH TLV | 3 mg/m3 as Resp. Dust | |
| | | OSHA PEL | 3 mg/m3 as Resp. Dust | |

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

Continued on page 2

5053Q

page 2

Section 4 -- FIRST AID MEASURES

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|----------------------------------------------|-------------------|--------------------------------|
| PRODUCT WEIGHT | 10.10 lb/gal | 1209 g/l |
| SPECIFIC GRAVITY | 1.22 | |
| BOILING POINT | 212 - 388 F | 100 - 197 C |
| MELTING POINT | Not Available | |
| VOLATILE VOLUME | 70 % | |
| EVAPORATION RATE | Slower than ether | |
| VAPOR DENSITY | Heavier than air | |
| SOLUBILITY IN WATER | N.A. | |
| pH | 9.0 | |
| VOLATILE ORGANIC COMPOUNDS (VOC Theoretical) | | |
| 0.80 lb/gal | 96 g/l | Less Federally Exempt Solvents |
| 0.25 lb/gal | 30 g/l | Emitted VOC |

Continued on page 4

5053Q

page 4

Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

TOXICOLOGY DATA

| CAS No. | Ingredient Name | | | | |
|------------|------------------|------|-----|-----|---------------|
| 107-21-1 | Ethylene Glycol. | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | 4700 mg/kg |
| 14464-46-1 | Cristobalite | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |
| 12001-26-2 | Mica | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Continued on page 5

5053Q

page 5

Section 14 -- TRANSPORT INFORMATION

No data available.

Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|----------|-------------------|---------|-----------|
| 107-21-1 | Ethylene Glycol. | 2 | |

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

=====
Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.