

## MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

Identification of the

preparation

HP Color LaserJet CE410A-X Black Print Cartridge

**Product use** This product is a black toner preparation that is used in HP LaserJet Pro 300 color M351/ HF

LaserJet Pro 400 color M451/ HP LaserJet Pro 300 color MFP M375/ HP LaserJet Pro 400 color MFP

M475 series printers.

Version # 02

**Revision date** 01-May-2012

Company identification Hewlett-Packard Company

> 3000 Hanover Street Palo Alto, CA 94304-1185

United States

Telephone 650-857-1501

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 **HP Customer Care Line** 

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

## 2. Hazards Identification

Acute health effects

Skin contact Unlikely to cause skin irritation. Eye contact May cause transient slight irritation

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust.

Use of this product as intended does not result in inhalation of excessive amounts of dust.

Ingestion Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

**Potential health effects** 

Routes of exposure Potential routes of exposure under normal use conditions are skin, eye contact and inhalation.

Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions.

Chronic health effects Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this

product as intended does not result in inhalation of excessive amounts of dust.

Carcinogenicity Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly

carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not

present this carcinogenic risk.

Other information This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive

1999/45/EC, as amended.

This preparation contains no component classified as Persistent, Bioaccumulative, and Toxic (PBT) or very Persistent and very Bioaccumulative (vPvB) as defined under Regulation (EC)

1907/2006.

# 3. Composition / Information on Ingredients

5. composition / 2ormation on 2g. carcing		
Components	CAS#	Percent
Styrene acrylate copolymer	Trade Secret	< 85
Carbon black	1333-86-4	< 10
Wax	Trade Secret	< 10
Amorphous silica	7631-86-9	< 3

Material name: CE410A-X MSDS US

12717 Version #: 02 Revision date: 01-May-2012 Print date: 01-May-2012

#### 4. First Aid Measures

First aid procedures

**Eye contact** Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at

least 15 minutes or until particles are removed. If irritation persists, consult a physician.

**Skin contact** Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

**Inhalation** Move person to fresh air immediately. If irritation persists, consult a physician.

**Ingestion** Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

### 5. Fire Fighting Measures

Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixtures when finely

dispersed in air.

**Extinguishing media** 

Suitable extinguishing

media

CO2, water, or dry chemical

Unsuitable extinguishing

media

None known.

**Protection of firefighters** 

Protective equipment and precautions for

firefighters

If fire occurs in the printer, treat as an electrical fire.

**Specific methods** None established.

**Hazardous combustion** 

products

Carbon monoxide and carbon dioxide.

#### 6. Accidental Release Measures

**Personal precautions** Minimize dust generation and accumulation.

**Environmental precautions** Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

**Other information** Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a

damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust

explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with

federal, state, and local regulations.

#### 7. Handling and Storage

**Handling** Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use

with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

**Storage** Keep out of the reach of children. Keep tightly closed and dry. Store away from strong oxidizers.

Store at room temperature.

#### 8. Exposure Controls / Personal Protection

#### **Occupational exposure limits**

#### **ACGIH**

Components	Туре	Value	Form
Carbon black (1333-86-4)	TWA	3.0000 mg/m3	Inhalable fraction.

#### **U.S. - Tennessee**

Components	Туре	Value	
Carbon black (1333-86-4)	TWA	3.5000 mg/m3	

#### **Exposure guidelines** USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10

mg/m3

Material name: CE410A-X MSDS US

**Engineering controls** Use in a well ventilated area.

Personal protective equipment

**General** No personal respiratory protective equipment required under normal conditions of use.

## 9. Physical & Chemical Properties

Fine powder **Appearance** Color Black.

Odor Slight plastic odor **Odor threshold** Not available.

**Physical state** Solid solid **Form** 

pН Not applicable **Melting point** Not available. Freezing point Not available. **Boiling point** Not applicable Flash point Not applicable Not applicable **Evaporation rate** Flammability limits in air, Not available.

upper, % by volume

Flammability limits in air, lower, % by volume

Not flammable

Not applicable Vapor pressure Vapor density Not available. Specific gravity 1 - 1.2 (H2O = 1)Relative density Not available.

Solubility (water) Negligible in water. Partially soluble in toluene and xylene.

**Auto-ignition temperature** Not applicable **Decomposition temperature** Not available.

176 - 266 °F (80 - 130 °C) Softening point

**Viscosity** Not applicable **Percent volatile** 0 % estimated VOC Not available.

Other information Decomposition temperature: > 200 ° C

#### 10. Chemical Stability & Reactivity Information

**Chemical stability** Stable under normal storage conditions. Conditions to avoid Imaging Drum: Exposure to light

**Incompatible materials** Strong oxidizers

**Hazardous decomposition** 

products

Carbon monoxide and carbon dioxide.

Possibility of hazardous Will not occur.

reactions

## 11. Toxicological Information

**Oral toxicity** LD50/oral/rat >2000 mg/kg; (OECD 401); Not harmful.. Not classified for acute oral toxicity

according to EU Directive 67/548/EEC and 1999/45/EC.

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group Carcinogenicity

2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation. None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.

Material name: CE410A-X MSDS US

12717 Version #: 02 Revision date: 01-May-2012 Print date: 01-May-2012

**ACGIH Carcinogens** 

Carbon black (CAS 1333-86-4) A3 Confirmed animal carcinogen with unknown relevance to

humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

IARC Monographs: Evidence of carcinogenicity in humans

Carbon black (CAS 1333-86-4) Inadequate data.

Inhalation toxicity No information available.

Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and

1999/45/EC.

Serious eye damage/eye

irritation

Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

**Chronic toxicity** No information available.

**Sensitization** Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA

HCS (US).

Mutagenicity Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Reproductivity Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65,

and DFG (Germany).

Symptoms and target organs Target Organs (NIOSH)

> Carbon black (CAS 1333-86-4) Eyes

> > Respiratory system

**Further information** Complete toxicity data are not available for this specific formulation

Refer to Section 2 for potential health effects and Section 4 for first aid measures.

12. Ecological Information

**Ecotoxicity** LC50: > 100 mg/l, Fish, 96.00 Hours

Persistence and degradability Not available.

Other adverse effects This product has not been tested for ecological effects.

13. Disposal Considerations

**Disposal instructions** Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely

dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state,

and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service

is available in your location, please visit http://www.hp.com/recycle.

14. Transport Information

**Further information** Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

15. Regulatory Information

**US federal regulations** US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

**CERCLA (Superfund) reportable quantity** 

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200

hazardous chemical

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

Material name: CE410A-X MSDS US

12717 Version #: 02 Revision date: 01-May-2012 Print date: 01-May-2012

Section 311 hazardous

chemical

No

**Regulatory information** All chemical substances in this HP product have been notified or are exempt from notification

under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea,

New Zealand, and China.

16. Other Information

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

**HMIS**® ratings Health: 1

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 1 Instability: 0

**Disclaimer** This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and

may not meet regulatory requirements in other countries.

**Issue date** 01-May-2012

**Manufacturer information** Hewlett-Packard Company

11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

**Explanation of abbreviations** 

**ACGIH** American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

**CFR** Code of Federal Regulations

**COC** Cleveland Open Cup

**DOT** Department of Transportation

**EPCRA** Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

**PEL** Permissible Exposure Limit

**RCRA** Resource Conservation and Recovery Act

**REC** Recommended

**REL** Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

**TCLP** Toxicity Characteristics Leaching Procedure

**TLV** Threshold Limit Value

TSCA Toxic Substances Control Act VOC Volatile Organic Compounds

Material name: CE410A-X MSDS US