Page 1 of 2

MSDS #: 56301

Sanford NA Emergency Medical Number: 888-786-0972
2707 Butterfield Road

Oak Brook, IL 60523 Creation Date: August 1, 2005

Phone: 630-481-2000 or 800-323-0749

Section One: Product Information

Product Name: Liquid Paper Correction Fluid - Smooth Coverage

Colors: Common White

Includes: Liquid Paper Multi Fluid Correction Fluid, (LPCF-19-13), Liquid Paper 2 in 1

Section Two: Composition

Titanium dioxide (13563-67-7), solvent naphtha (64742-89-8), mineral spirits (64742-48-9), resins, dispersant, colorants, fragrance

Section Three: Hazards Identification

If vapors are deliberately inhaled, the following symptoms may occur: respiratory irritation, dizziness, drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma, and death.

Section Four: First Aid Measures

Inhalation: This product is considered safe under normal use conditions.

Skin Contact: Wash with soap and water.

Eye Contact: Irritation may occur. Wash through with water.

Ingestion: Contact a physician. NOTE TO PHYSICIAN: Contains solvent naphtha and mineral spirits, which may cause

chemical pheumonitis.

Section Five: Fire Fighting Measures

Flash Point: 27F (Closed Cup)

Flammability Limits (% by volume): Lower: 1% Upper: 8%

Extinguishing Media: Dry chemical, foam, carbon dioxide.

Special Fire Fighting Measures: In fires involving large quantities, use self-contained breathing apparatus. Cool fire-exposed

containers with water spray/fog.

Unusual Fire and Explosion

Hazards:

Product is flammable. May produce hazardous decomposition products.

Section Six: Accidental Release Measures

In Case of Spill or Accidental Release: Wipe up with absorbent material.

Section Seven: Handling and Storage

Handling: No special handling requirements.

Storage: In large quantities, store in a well-ventilated area.

MSDS #: 56301

Section Eight: Exposure Controls and Personal Protection

Eye Protection: None under normal use conditions. Clothing: None under normal use conditions. None under normal use conditions. Respirator: Ventilation: None under normal use conditions.

Section Nine: Physical and Chemical Properties

For product unless otherwise specified:

209 - 230F **Boiling Point:** ~1.2 Specific Gravity:

Vapor Pressure: 124 mm Hg at 100F

Solubility in Water: Negligible

Evaporation Rate: 3.6 (butyl acetate = 1) Appearance; Odor: White fluid; solvent odor

Section Ten: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Open flames or other ignition sources.

Chemical Incompatibility: Strong oxidizers

Hazardous Decomposition: May produce oxides of carbon, nitrogen, and various hydrocarbons in fire.

Hazardous Polymerization: Will not occur

Section Eleven: Toxicological Information

IARC Monographs: No National Toxicology Program: Nο OSHA Regulated:

Section Twelve: Ecological Information

Not available

Section Thirteen: **Disposal Considerations**

Dispose in accordance with Federal, State, and Local Regulations.

Section Fourteen: Transport Information

ORM-D Consumer Commodity

Flammable Liquid, n.o.s., (petroleum distillates), Class 3, UN1993, PGII (25.5F CC), Ltd. Qtys, EmS#3-07

Consumer Commodity, 9, ID8000, packing instruction 910

Section Fifteen: **Regulatory Information**

TSCA INVENTORY: The product on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory.

All ingredients used to manufacture this product are listed on the TSCA Inventory

Section Sixteen: Other Information

N/A

HMIS Code

Health 2 Flammability 3 Reactivity 0

Personal Protection 0=Minimal / 4 = Severe

Sanford NA has been advised by Counsel that the OSHA Hazard Communication Standard does not apply to the Sanford Product described in this Material Safety Data Sheet. The reason for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2004 per the Code of Federal Regulations. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by the Hazard Communication Standard nor is this MSDS meant to comply with all requirements of the Hazard Communication Standard.