

MATERIAL SAFETY DATA SHEET

• •	
Material name	HP Color LaserJet Q6472A Yellow Print Cartridge
Use of the preparation	This product is a yellow toner preparation that is used in HP Color LaserJet 3600 series printers.
Version #	05
Revision date	03-08-2009
Company identification	Hewlett-Packard Company 3000 Hanover Street Palo Alto, CA 94304-1185 United States Telephone 650-857-1501
	Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209 (Direct) 1-503-494-7199 HP Customer Care Line (Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551 Email: hpcustomerinquiries@hp.com
Date prepared	Mar 08, 2009
MSDS number	354691
lazards Identification	
Acute health effects	
Skin contact	Unlikely to cause skin irritation.
Eye contact	May cause transient slight irritation
Inhalation	Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust.
Ingestion	Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.
Potential health effects	
Routes of exposure	Potential routes of exposure under normal use conditions are skin and eye contact; and inhalation
Routes of exposure	
Routes of exposure Chronic health effects	inhalation Ingestion is not expected to be a primary route of exposure for this product under normal us
	inhalation Ingestion is not expected to be a primary route of exposure for this product under normal us conditions. Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this
Chronic health effects	 inhalation Ingestion is not expected to be a primary route of exposure for this product under normal us conditions. Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this product as intended does not result in inhalation of excessive amounts of dust. None of the ingredients have been classified as carcinogens according to EU, IARC, MAK,

3. Composition / Information on Ingredients

Component/substance	CAS number	% by weight	
Styrene acrylate copolymer	Trade Secret	< 85	
Wax	Trade Secret	< 15	
Pigment	Trade Secret	< 5	
Amorphous silica	7631-86-9	< 2	

4. First Aid Measures

at least 15 minutes or until particles are removed. If iritation persists, consult a physical Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if in develops or persists. Inhalation Move person to fresh air immediately. If irritation persists, consult a physician. Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, co physician. 5. Fire Fighting Measures Flash point and method Not applicable Carbon monoxide and carbon dioxide. products Carbon monoxide and carbon dioxide. Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Extinguishing media Suitable extinguishing media Suitable extinguishing media Unsuitable extinguishing media Unsuitable extinguishing media Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Protection of firefighters Protective equipment and precautions for firefighters Protective equipment and precautions If fire occurs in the printer, treat as an electrical fire. Social firefighting procedures None established. 6. Accidental Release Measures Personal precautions Personal precautions Minimize dust generation and accumulatio	FIRST AID Measures	
at least 15 minutes or until particles are removed. If irritation persists, consult a physician. Inhalation Move person to fresh air immediately. If irritation persists, consult a physician. Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, corphysician. 5. Fire Fighting Measures Flash point and method Hazardous combustion Carbon monoxide and carbon dioxide. products Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Extinguishing media C02, water, or dry chemical Suitable extinguishing media C02, water, or dry chemical Unsuitable extinguishing media Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Protection of firefighters Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Protection of firefighters Hire occurs in the printer, treat as an electrical fire. Protection of firefighters Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations. Do not flush into surface water or maxplosive dust-air mixture finely divy vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder ca	First aid procedures	
develops or persists. Move person to fresh air immediately. If irritation persists, consult a physician. S. Fire Fighting Measures Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, corphysician. S. Fire Fighting Measures Carbon monoxide and carbon dioxide. Flash point and method Not applicable Hazardous combustion Carbon monoxide and carbon dioxide. products Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Extinguishing media CO2, water, or dry chemical Unsuitable extinguishing media None known. Unsuitable extinguishing media None known. Unsuitable extinguishing media None known. Protection of firefighters Protection of firefighters Protection of firefighters None established. 6. Accidental Release Measures Minimize dust generation and accumulation. Environmental precautions Minimize dust generation and accumulation. Other information Slowip vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. Other information Slowiy vac	Eye contact	Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.
Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, corphysician. 5. Fire Fighting Measures Flash point and method Not applicable Flash point and method Carbon monoxide and carbon dioxide. products Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Extinguishing media CO2, water, or dry chemical Unusual fire and explosion hazard None known. Protection of firefighters None known. Protective equipment and precautions for firefighters If fire occurs in the printer, treat as an electrical fire. Protective equipment and precautions Minimize dust generation and accumulation. Do fi information Slowy vacuum or sweep the material into a bag or other sealed container. Clean rem with adamp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosive or with federal, state, and local regulations. Other information Slowy vacuum or sweep the material into a bag or other sealed container. Clean rem with adequate ventilation. Keep away from excessive heat, sparks, and open flames Keep out of the reach of children. Store at nom temperature. Store away from store with adequate ventilation. Keep away from excessive heat, sparks, and open flames Keep out of the reach of children. Store at room temperature. Store away from store oxidaters. Keep tightly closed and dry. 8. Exposure Controls / Personal Pro	Skin contact	Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists.
strice physician. 5. Fire Fighting Measures Flash point and method Flash point and method Not applicable Hazardous combustion Carbon monoxide and carbon dioxide. products Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Extinguishing media Suitable extinguishing media Suitable extinguishing media CO2, water, or dry chemical Unusual fire and explosion hazard None known. Inazurat Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Protection of firefighters Protective equipment and precautions for firefighters None established. None established. 6. Accidental Release Measures Personal precautions Personal precautions Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean re explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin an	Inhalation	Move person to fresh air immediately. If irritation persists, consult a physician.
Flash point and method Not applicable Flash point and method Not applicable Carbon monoxide and carbon dioxide. Carbon monoxide and carbon dioxide. Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Extinguishing media CO2, water, or dry chemical Unsuitable extinguishing media None known. Unusual fire and explosion hazard None known. Protection of firefighters Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Protection of firefighters If fire occurs in the printer, treat as an electrical fire. Protective equipment and precautions Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. 7. Handling Magnet Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage Keep out of the reach of children. Store at ro	Ingestion	Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a physician.
Hazardous combustion products Carbon monoxide and carbon dioxide. Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Extinguishing media Suitable extinguishing media CO2, water, or dry chemical Unsuitable extinguishing media None known. Unsuitable extinguishing media None known. Unsuitable extinguishing media None known. Unsuitable extinguishing media If fire occurs in the printer, treat as an electrical fire. Protection of firefighters Protective equipment and precautions for firefighters If fire occurs in the printer, treat as an electrical fire. Personal precautions Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rer with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (R	Fire Fighting Measures	
products Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Extinguishing media CO2, water, or dry chemical Suitable extinguishing media None known. Unsuitable extinguishing media None known. Protection of firefighters Frotective equipment and precautions for firefighters Special firefighting procedures None established. 6. Accidental Release Measures Personal precautions Personal precautions Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proc. Fine powder can form explosive heat, sark, and open flames. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from strom oxidzers. Keep out of the reach of children. Store at room temperature. Store away from strom oxidzer	Flash point and method	Not applicable
finely dispersed in air. Extinguishing media Suitable extinguishing media Unsuitable extinguishing media Unusual fire and explosion hazard Protection of firefighters Protective equipment and precautions for firefighters Special firefighting procedures None established. 6. Accidental Release Measures Personal precautions Environmental precautions Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. 7. Handling and Storage Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames, Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. 8. Exposure Controls / Personal Protection Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 m		Carbon monoxide and carbon dioxide.
Suitable extinguishing media CO2, water, or dry chemical Unsuitable extinguishing media None known. Unsual fire and explosion hazard Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Protection of firefighters If fire occurs in the printer, treat as an electrical fire. Protective equipment and precautions for firefighters If fire occurs in the printer, treat as an electrical fire. Personal precautions Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rer with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulat Amorphous silica: USA OSHA (TWA/PEL): 20 mpcf 80 (mg/m3)%SIO2, ACGIH	Flammable properties	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.
media Like most organic material in powder form, toner can form explosive dust-air mixture finely dispersed in air. Protection of firefighters Protective equipment and precautions for firefighters Special firefighting procedures None established. 6. Accidental Release Measures Personal precautions Personal precautions Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rent with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in cont with federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SIO2, ACGIH	Suitable extinguishing	CO2, water, or dry chemical
hazard finely dispersed in air. Protection of firefighters Protective equipment and precautions for firefighters Special firefighting procedures If fire occurs in the printer, treat as an electrical fire. Special firefighting procedures None established. 6. Accidental Release Measures Personal precautions Personal precautions Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispos considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rer with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH		None known.
Protective equipment and precautions for firefighters If fire occurs in the printer, treat as an electrical fire. Special firefighting procedures None established. 6. Accidental Release Measures Personal precautions Personal precautions Minimize dust generation and accumulation. Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Particulate, Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH		Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.
precautions for firefighters Special firefighting procedures None established. 6. Accidental Release Measures Personal precautions Environmental precautions Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean ren with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. 7. Handling and Storage Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Protection of firefighters	
6. Accidental Release Measures Personal precautions Minimize dust generation and accumulation. Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean remwith a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in conwith federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH		If fire occurs in the printer, treat as an electrical fire.
Personal precautions Minimize dust generation and accumulation. Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Dispose considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean rem with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in con with federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Special firefighting procedures	None established.
Environmental precautionsDo not flush into surface water or sanitary sewer system. See also section 13 Dispositions.Other informationSlowly vacuum or sweep the material into a bag or other sealed container. Clean remwith a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in conwith federal, state, and local regulations.7. Handling and Storage Handling StorageKeep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.8. Exposure Controls / Personal Protection Exposure guidelinesUSA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Accidental Release Measures	
Environmental precautionsDo not flush into surface water or sanitary sewer system. See also section 13 Dispositions.Other informationSlowly vacuum or sweep the material into a bag or other sealed container. Clean remwith a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in conwith federal, state, and local regulations.7. HandlingKeep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames.8. Exposure Controls / Personal ProtectionUSA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Personal precautions	Minimize dust generation and accumulation.
with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in conwith federal, state, and local regulations. 7. Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulat Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	-	Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.
Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), 3 mg/m3 (Respirable Particulate), 3 mg/m3 (Respirable Particulate)	Other information	Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations.
Storage with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Storage Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. 8. Exposure Controls / Personal Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Handling and Storage	
oxidizers. Keep tightly closed and dry. 8. Exposure Controls / Personal Protection Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), 3 mg/m3 (Respirable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Handling	Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Us with adequate ventilation. Keep away from excessive heat, sparks, and open flames.
Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Storage	Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.
ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particula Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Exposure Controls / Personal P	Protection
Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH	Exposure guidelines	USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)
		ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)
Personal protective equipment General No personal respiratory protective equipment required under normal conditions of us		No personal respiratory protective equipment required under normal conditions of use.



MATERIAL SAFETY DATA SHEET

9. Physical & Chemical Properties

 Appoaranco	Fine nowder
Appearance	Fine powder Yellow
Color	
Odor	Slight plastic odor
Odor threshold	Not available.
Physical state	Not available.
Form	solid
рН	Not applicable
Melting point	Not available.
Freezing point	Not available.
Boiling point	Not applicable
Flash point	Not applicable
Evaporation rate	Not applicable
Flammability	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not flammable
Vapor pressure	Not applicable
Vapor density	Not applicable
Specific gravity	1 - 1.2 (H2O = 1)
Relative density	Not available.
Solubility (water)	Negligible in water. Partially soluble in toluene and xylene.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available.
Softening point	212 - 302 °F (100 - 150 °C)
Viscosity	Not applicable
Chamical Stability & Depativity	

10. Chemical Stability & Reactivity Information

Chemical stability	Stable under normal storage conditions.
Conditions to avoid	Imaging Drum: Exposure to light
Incompatible materials	Strong oxidizers
Hazardous decomposition products	Carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	Will not occur.
11. Toxicological Information	
Oral toxicity	LD50/oral/rat >2000 mg/kg; (OECD 401); Not harmful Not classified for acute oral toxicity according to EU Directive 67/548/EEC and 1999/45/EC.
Inhalation toxicity	No information available.
	Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and 1999/45/EC.
Eye irritation	Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU Directive 67/548/EEC and as amended.

UP I	MATERIAL SAFETY DATA SHEET
invent	
Sensitization	Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA HCS (US).
Chronic toxicity	No information available.
Carcinogenicity	Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA Regulations (USA), EU Directive, or Proposition 65 (California).
Mutagenicity	Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)
Reproductive toxicity	Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65, and DFG (Germany).
12. Ecological Information	
Ecotoxicity	96.00 Hours, LL50 > 1000 mg/l, rainbow trout
Persistence and degradability	Not available.
13. Disposal Considerations	
Disposal instructions	Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.
	HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.
14. Transport Information	
Not available.	
General	Not a regulated article under United States DOT, IATA, ADR, IMDG, or RID.
15. Regulatory Information	
US federal regulations	US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders under TSCA.
CERCLA (Superfund) reportabl None	le quantity
Superfund Amendments and Reauthorization Act of 1986 (SARA)	
Superfund Amendments and R	Reauthorization Act of 1986 (SARA)
Superfund Amendments and R Hazard categories	Reauthorization Act of 1986 (SARA) Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
-	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No
Hazard categories Section 302 extremely	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
Hazard categories Section 302 extremely hazardous substance Section 311 hazardous	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No No
Hazard categories Section 302 extremely hazardous substance Section 311 hazardous chemical	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No No No All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South
Hazard categories Section 302 extremely hazardous substance Section 311 hazardous chemical International regulations	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No No No All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South
Hazard categories Section 302 extremely hazardous substance Section 311 hazardous chemical International regulations	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No No No All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.
Hazard categories Section 302 extremely hazardous substance Section 311 hazardous chemical International regulations 16. Other Information HMIS® ratings	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No No No All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.



MATERIAL SAFETY DATA SHEET

Replaces sheet dated Disclaimer

Jun 18 2008 3:23PM

This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

MSDS sections updated Hazards Identification: Other information

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds
Manufacturer information	Hewlett-Packard Company 11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199 (Toll-free within the US) 1-800-457-4209